

1. Identification of the substance/preparation and company/undertaking.

TRADE NAME: N50XL-A, -B, -C, -D

INK NAME: U-2

Color: A:BLACK(BK), B:RED(R), C:BLUE(BL), D:GREEN(G)

Relevant identified uses of the substance or mixture and uses advised against:

Xylene based dye ink.

Manufacturer/Supplier

TAISEI CO.,LTD.

986-1,2-CHOME,YASHIO CITY,SAITAMA PREF.340-0811,JAPAN

Tel: (81) 48-996-9503

Fax: (81) 48-997-1245

Information department: (81) 48-996-9503

Emergency telephone number: (81) 48-996-9503

2. Hazards identification.**Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008****GHS classification**

Flam. Liq. 3 STOT RE 1
Skin Corr. 2 Asp. Tox. 1
Eye Irrit. 2 Aquatic Acute 1
Carc. 2 Aquatic Chronic 2
STOT SE 2

Label elements

GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environment

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H371 May cause damage to organs.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.