



DISPLAY

Screen Size and Resolution	65" 4K 75" 4K 86" 4K
Screen Type	TFT LCD (Direct LED Backlight)
Blue Light Reduction	Yes
Bonded Glass	Yes
Aspect Ratio	16:9
Display Area	65" 4K: 1429 x 804 mm (56.3 x 31.7 in) 75" 4K: 1652 x 930 mm (65 x 36.6 in) 86" 4K: 1895 x 1066 mm (74.6 x 41.9 in)
LCD Viewing Angle	178°
LCD Response Time	8 ms
LCD Refresh Rate (Panel)	60 Hz
LED Lifespan	50,000 hours
Contrast Ratio	5000:1 Dynamic 1200:1 Static
Brightness	400 cd/m2
Ambient Light Sensor	Yes
Glass Hardness	9H (pencil) , 7 (Mohs)
Glass Type	Heat tempered, Anti-Glare

INTERACTIVITY

Vellum Touch Technology	Yes
Continuous Touch Points	20
Touch Resolution	32768 x 32768 px
Response Time	10 ms
Touch Accuracy	1 mm
Tracking Rate	4 m/s
Scan Rate	200 Hz
Gestures and Edge Swipes	Windows® supported
Unique Pen IDs	1
Pen and Touch Differentiation	Yes
Palm Erase	Yes
Palm Rejection	Yes
Pens Included	Yes, 2
Pen Type	Battery-less pen
Pen Holder	Integrated full-length pen tray
Pen Tip Diameter	3 mm
Classroom Essential Apps	Including Whiteboard, Annotate, Timer, Spinner, Screen Capture, Screen Share, Browser, PDF Reader, Media Player
Compatibility	Windows® 7 to 11; Mac OS® 10.8 to 10.11; macOS® Sierra 10.12.1 or later; Linux® Ubuntu 20.04 LTS; Chrome OS™

COMPUTING

Operating System	ActivPanel OS
RAM	4 GB
Internal Storage	32 GB
CPU	ARM CORTEX - A73 x 4
GPU	ARM Mali-G71 MP3
Trusted Platform Module	Yes
Cloud Based User Profiles	Yes

AUDIO

	0 45.11
Dual Front-facing Speakers	2 x 15 W

CONNECTIVITY

OPS Slot	1
HDMI In (Rear)	2 (2.0)
HDMI In (Front)	1 (2.0)
Display Port	1 (1.2)
USB-A 2.0 (Rear)	1
USB-C 3.2 (Rear)	1 (60 W Power Delivery)
USB-B 3.0 (Touch, Front)	1
USB-B 3.0 (Touch, Rear)	3
USB-A 3.0 (Front)	2
USB-A 3.0 (Rear)	2
MicroSD Slot	Yes
LAN In (RJ45)	1 Gbps
LAN Out (RJ45)	1 Gbps
Wake-on-LAN	Yes
Wi-Fi (Client)*	IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6 and dual band supported
Bluetooth*	5.0
HDMI Out	1 (2.0)
AV-In (3.5 mm)	1
Mic (3.5 mm)	1
Audio Out (3.5 mm)	1
RS-232	1
* Not included	

PANEL MANAGEMENT

OTA Updates	Yes
Promethean Panel Management	Yes

ActivPanel 9 2022 SS 06/22 v1.3 EN-INTL



POWER

100 V - 240 V AC
65" 4K: 128 W 75" 4K: 141 W 86" 4K: N/A
<= 0.5 W
Yes

ENVIRONMENTAL

Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage Temperature	-15 °C to 55 °C (-5 °F to 131 °F)
Operating Humidity	20% to 80% non-condensing humidity
Storage Humidity	20% to 90% non-condensing humidity

COMPLIANCE & CERTIFICATION

Regulatory Certifications	CE, FCC, IC, UL, CUL, CB, RCM
Energy Star Certified	65" 4K: Yes 75" 4K: Yes
	86" 4K: No

PHYSICAL SPECIFICATIONS

Panel Dimensions	65": 1509 x 946 x 113 mm (59.4 x 37.2 x 4.4 in) 75": 1730 x 1070 x 113 mm (68.1 x 42.1 x 4.4 in) 86": 1975 x 1208 x 113 mm (77.8 x 47.6 x 4.4 in)
Packed Dimensions	65": 1660 × 1045 × 220 mm (65.4 x 41.1 x 8.7 in) 75": 1900 × 1160 × 225 mm (74.8 x 45.7 x 8.9 in) 86": 2160 × 1310 × 225 mm (85 x 51.6 x 8.9 in)
Panel Net Weight	65": 43.2 kg (95.3 lb) 75": 55.3 kg (121.9 lb) 86": 69.6 kg (153.4 lb)
Packed Weight	65": 51.4 kg (113.3 lb) 75": 65.8 kg (145.1 lb) 86": 84.4 kg (186.1 lb)
VESA Mount Point	65": 600 x 400 mm (23.6 x 15.7 in) 75": 800 x 400 mm (31.5 x 15.7 in) 86": 800 x 600 mm (31.5 x 23.6 in)

EDUCATION SOFTWARE LICENCE

ActivInspire® Professional	Included
Single User	

PACKED CONTENTS

What's in the Box	1x ActivPanel 9
	1x 3 m Length HDMI Cable
	1x 3 m Length USB Cable (A-B)
	1x 3 m Regional Power Cable
	1x 2 m Length USB-C Cable
	1x Remote Control
	2x Batteries for Remote
	2x Pens
	1x Sealed Antistatic Bag
	8x Desiccant
	4x VESA Mount Screws (M6)
	1x Mini PC Bracket with Screws (x2)
	1x Quick Install Guide

INSTALLATION

The installation of this product should be completed by a qualified installer. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit Support.PrometheanWorld.com.

WARRANTY

 $Warranty\ term\ and\ upgrade\ options\ vary\ by\ region.\ Contact\ your\ local\ reseller\ or\ distributor\ for\ information\ and\ visit\ Promethean World.com/Warranty.$

SUPPORT

 $For all \ Promethean \ products, visit \ Support. Promethean World. com.$


ActivPanel 9 2022 SS 06/22 v1.3 EN-INTL Page 2



TECHNICAL DRAWINGS


65″


Front



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	1640	64.6
В	1429	56.3
С	805	31.7
D	131	5.2
Е	88	3.5
F	946	37.2
G	1509	59.4
Н	600	23.6
I	400	15.7


Back









TECHNICAL DRAWINGS



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	1897	74.7
В	1652	65.0
С	930	36.6
D	130	5.1
Е	88	3.5
F	1070	42.1
G	1730	68.1
Н	800	31.5
I	400	15.7





Back


ActivPanel 9 2022 SS 06/22 v1.3 EN-INTL Page 4




TECHNICAL DRAWINGS


86"

Front



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
Α	2177	85.7
В	1897	74.7
С	1068	42.0
D	132	5.2
Е	88	3.5
F	1208	47.6
G	1975	77.8
Н	800	31.5
I	600	23.6





Back

ActivPanel 9 2022 SS 06/22 v1.3 EN-INTL Page 5